

# eBridge16CR – IP over Coax Receiver



The eBridge16CR is a 16 channel ethernet over coax rack mount receiver. The eBridge16CR enables fast 10/100Base-T Ethernet digital communication to be transmitted over coax cable. This unit is designed to be used with eBridge1CT transceivers. This plug and play unit facilitates system upgrades from analog to IP cameras/devices utilizing existing legacy Coax and eliminating the costs and labor associated with installing new network cabling. In addition the use of coax enables data transmission to be extended over 1500' (over four times the 100m/328 ft Ethernet maximum length), eliminating the need for repeaters. At the same time the units can combine Composite Video Signal with the Ethernet data enabling connection to an analog input on a monitor or matrix switch.

## Specifications

### SLOC™ Compliant:

- Incorporates \*sloc™ (Security Link over Coax) technology.

### Input:

- 24VDC to 56VDC UL Listed Class 2 power supply (polarity not observed) or UL Listed 24VAC Class 2 plug-in transformer.

### Power Consumption:

- 24VDC/1500mA, 56VDC/700mA, 24VAC/2200mA.

### Ethernet:

- Sixteen (16) RJ45 ethernet channels.
- Connectivity: RJ45, auto-crossover.
- Wire type: 4-pair Cat-5 or higher structured cable.
- Distance: up to 328 ft. (100m).
- Speed: 10/100BaseT, half/full duplex, auto negotiation.

### Coax:

- Sixteen (16) BNC input channels.
- Sixteen (16) BNC composite video output channels.
- Distance: up to 1,500 ft.
- Connectivity: BNC, RG-59/U or similar.

### LED Indicators:

- Blue LED - Coax link connection.
- Yellow and Green LED (RJ45) IP Link status, 10/100Base-T/active.
- Green LED - Power.

### Environmental:

- Operating Temperature: 14°F to 122°F (-10°C to +50°C).
- Storage Temperature: -22° to 158°F (-30° to +70°C) Storage.
- Humidity: 20 to 85%, non-condensing.

### Electrical:

- BTU/Hr.:
  - 24VDC: 18.43 BTU/Hr.
  - 56VDC: 20.06 BTU/Hr.
  - 24VAC: 27.02 BTU/Hr.

### Applications:

- Retrofit digital IP cameras in an analog CCTV installation.
- Works with Megapixel, HD720, HD1080 and VGA (SD) cameras.
- Extend Network link distance in an industrial environment.
- Upgrade deployed CCTV Coax to a digital network for Retail, Casinos, Airports, Schools, Hospitals, etc.
- Simultaneously use Composite Video matrix switch for monitor display and control, while the NVR is used for digital IP camera recording.
- eBridge is rated to pass 25mbps of data at distances up to 1500 ft. With proper headend equipment, multiple Megapixel cameras can be used.

### Mechanical:

- 1U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 1.625" x 19.125" x 8.5" (41.275 mm x 486 mm x 216 mm)
- Product weight (approx.): 6.17 lbs. (2.8 kg).
- Shipping weight (approx.): 7.47 lbs. (3.39 kg).

### Units available individually:

- **eBridge1CT:** Ethernet transceiver enables IP video/data over Coax. Unit operates with eBridge1CR and eBridge16CR receivers.

\* sloc is a registered trademark of Intersil Corporation.



UL/CUL Listed for Information  
Technology Equipment (UL 60950-1).



C-Tick Approved - Z1409



European Conformity

© 2013 Sony Corporation. All rights reserved. Reproduction in whole or in part without permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measurements are approximate. Sony, 'make.believe', IPELA, DEPA, Exmor and their respective logos are trademarks of Sony Corporation. HDMI and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other trademarks are the property of their respective owners.

#### About Sony PSE

Sony PSE is the leading supplier of AV/IT solutions to businesses across a wide variety of sectors including, **Media and Broadcast, Video Security and Retail, Transport & Large Venue markets**. It delivers products, systems and applications to enable the creation, manipulation and distribution of digital audio-visual content that add value to businesses and their customers. With over 25 years' experience in delivering innovative market-leading products, Sony PSE is ideally placed to deliver exceptional quality and value to its customers. Sony's PSE division, its systems integration arm, offers its customers access to the expertise and local knowledge of skilled professionals across Europe. Collaborating with a network of established technology partners, Sony PSE delivers end to end solutions that address the customer's needs, integrating software and systems to achieve each organisations' individual business goals. For more information please visit [www.pro.sony.eu](http://www.pro.sony.eu)